

12V SEALED LEAD ACID BATTERIES

FEATURES

- Absorbent Glass Matt (AGM) technology for superior performance
- Valve regulated, spill proof construction allows safe operation in any position
- Power/Volume ratio yielding unrivaled energy density
- Rugged impact resistant ABS case and cover (UL94-HB)
- Approved for transport by air. D.O.T., I.A.T.A., F.A.A and C.A.B certified
- UL recognized under file name MH 20845

WARRANTY

A battery determined to be defective within the warranty period shall be repaired or replaced at a cost equal to the net price in effect at the time, reduced by the percentage in effect by prorating. Warranty is void if batteries are not maintained and/or installed according to specifications. Liability extends to the repair/replacements of the battery only, buyer is responsible for all costs to de-install defective products and re-install defective product and re-install replacement repaired products. For full warranty details, visit our Warranty Section.



Series	Volt	Amp	Dimensions	Dimension Image
B12V7A	12V	7Ah	A - 2.56"	Dia Dia
			B - 3.86"	
			C - 5.95"	POWERS SONIC.
			D - 3.7"	MODIL PLANETS DE D
B12V12A	12V	12Ah	A - 3.86"	[]p
			B - 3.86"	
			C - 5.94"	POWER DES STATES B D D
			D - 3.66"	, Z & .
B12V23A	12V	2.3Ah	A94"	ŢA
			B – 2.56"	
			C - 7.17"	Manual Property Barriers Barri
			D-2.4"	- c
B12V33A	12V	33Ah	A - 5.14"	1 A
			B-7"	
			C - 7.72"	POSICE PS SOURCE
			D - 6.22"	- C
B12V55A	12V	55Ah	A - 5.45"	
			B - 8.98"	
			C - 9.04"	
			D - 8.15"	2.5 %