


FEATURES

- Full Range of voltage and amperage capacities
- Operating temperatures range of 32°F (0°) to 122°F (50°)

WARRANTY

A battery determined to be defective within the warranty period shall be repaired or replaced at a cost equal to the net price in effect at the time, reduced by the percentage in effect by prorating. Warranty is void if batteries are not maintained and/or installed according to specifications. Liability extends to the repair/replacements of the battery only, buyer is responsible for all costs to de-install defective products and re-install defective product and re-install replacement repaired products. For full warranty details, visit our Warranty Section.



Ordering information								
Series	Volt	Amp	Cells	Length	Height	Width	Diameter	Image
BA-45A	1.2	1200	2	1.625"			.625"	
BA-AA	1.2	700	2	1.875"			.5"	
BAA-12	1.2	1000	1	1.875"			.563"	
BAA-24	2.4	700	2	3.8125"			.563"	
BAA-36	3.6	700	3	1.875"	1"	1.125"		
BAA-36900	3.6	900	3	1.875"	1"	1.125"		
BAA-3618	3.6	1800	3	1.875"	1"	1.125"		
BAA-36S	3.6	700	3	5.75"			.563"	
BAA-48	4.8	700	4	1.875"	.563"	1.125"		
BAA-48R	4.8	700	4	1.875"	1.125"	1.125"		
BAA-48R500	4.8	500	4	1.875"	1.125"	1.125"		
BAA-48R900	4.8	900	4	1.875"	1.125"	1.125"		
BAA-48S	4.8	700	4	3.8125"	.563"	1.125"		
BAA-6	6	700	6	1.875"	1"	1.625"		
BAA-96	9.6	700	8	7.688"	.563"	1.125"		
B23AA-48	4.8	400	1	1.125"	1.125"	1.125"		

