



VALUE GRADE CAST ALUMINUM UNIVERSAL LED EXIT SIGN | RED/GREEN SELECTABLE | BATTERY-BACKUP

Code: CALUM-U



Clean lines, durable material and energy saving LEDs make this unit one of our best selling exit sign series! Available in a variety of colors to complement your space.



Compatible Battery: 4.8V 700mAh NiCAD

FEATURES

- UL 924, NEC, NFPA 101, and NFPA 70 Life Safety Code
- Compliant CEC Title 20
- Listed for damp location
- Universal 120-277VAC Operation
- 4.8V 700mAh Ni-Cad Battery
- LED Energy savings
- Universal canopy included
- Spec grade cast aluminum housing
- Universal knock-out chevrons
- Push-to-test switch
- Charge rate / power on LED indicator light

WARRANTY INFORMATION

Any component that fails due to manufacturer's defect is guaranteed for 1 year. The warranty only covers products installed and maintained in accordance with the instructions provided by their respective manufacturer and no warranty is made with respect to any of our products that are otherwise installed or maintained. For full warranty details, visit our Warranty Section.

Conformance to Codes and Standards

The CALUM series is UL listed and meets or exceeds the following: UL 924, NEC, OSHA and NFPA 101 Life Safety Code requirements.

ORDERING INFORMATION

Series	Letter Color	Faceplate/ Housing Color	Operation Type	Sides
CALUM	R/G (Red / Green Selectable)	A (Brushed Aluminum / Brushed Aluminum)	Battery Backup	U (Single / Double)

CONSTRUCTION

The CALUM sign features a decorative design with a die-cast aluminum housing. Includes universal faceplates for both single and double face configurations, and displays 6-inch EXIT letter height with a 3/4-inch stroke and optional knockout chevron directional arrows.

ILLUMINATION

Illumination is achieved using long-lasting, energy-efficient ultra-bright LEDs. A color-matched diffuser eliminates hot spots and striations, ensuring optimal light distribution. The sign features a **field-selectable red or green** LED circuit board. The default factory setting is red.

ELECTRICAL COMPONENTS

Universal voltage input of 120-277VAC with 60Hz operation. The unit features an LED display that indicates AC power status (AC/ON) and includes an external push-button test switch for quick operational checks of battery backup functionality. Units offers surge protection.

EMERGENCY OPERATION

Upon failure of the normal utility power, an internal solidstate transfer switch automatically provides uninterrupted emergency operation for at least 90 minutes. Battery begins recharging when power is restored.

BATTERY - BATTERY BACKUP

The CALUM series is designed with a maintenance-free 4.8V 700mAh NiCad battery that provides a minimum emergency duration of 90 minutes, with a full recharge time of 24 hours.

ELECTRICAL INFORMATION

Series	Input Voltage	Power Consumption	Current	Discharge Duration
CALUM-U	120VAC 60Hz	3.4W	32mA	90 Minutes
	277VAC 60Hz	3.5W	15mA	90 Minutes

OPERATIONAL TEMPERATURE

Temperature Ratings	
Battery Backup	32°F to 104°F

INSTALLATION

The CALUM is suitable for surface wall, side and ceiling mounting via included canopy. Snap together design allows for quick and easy installation. Knock-out chevrons for customized egress signage.

DIMENSIONS

