



THIN HIGH OUTPUT LED EMERGENCY LIGHT | 600 LUMEN | ADJUSTABLE LAMPS

Code: EL-THO



The EL-THO series combines traditional emergency lighting and energy efficiency LED performance with a thin, low profile design.



Compatible Battery: 3.6V 7200mAh

Compatible Remote Head(s): [RHP-L-3V](#), [RHB-L-MV](#), [RHB-WPL-MV](#)

To use with remote heads, please change the **Operation Type** above to **Battery Backup + Remote Head Capable** to ensure compatibility. Code at time of checkout must read: **EL-THO-W-RH**.

FEATURES

- UL 924, NEC, OSHA and NFPA 101 Life Safety Code
- Listed for damp location
- Two fully adjustable, glare-free LED lighting heads
- LED indicator light with push-to-test switch
- Lightweight, injection molded, 5VA flame retardant thermoplastic housing
- 100-300 VAC operation
- Universal mounting plate
- Short circuit, voltage surge, brown out and low battery voltage disconnect protected

WARRANTY INFORMATION

Any component that fails due to manufacturer's defect is guaranteed for 1 year. The warranty only covers products installed and maintained in accordance with the instructions provided by their respective manufacturer and no warranty is made with respect to any of our products that are otherwise installed or maintained. For full warranty details, visit our Warranty Section.

Conformance to Codes and Standards

The EL-THO series is UL listed and meets or exceeds the following: UL 924, NEC, OSHA and NFPA 101 Life Safety Code requirements.

ORDERING INFORMATION

Series	Housing Color	Operation Type
EL-THO	W (White)	BB (Battery Backup)
		RH (Remote Head Capable)

CONSTRUCTION

The EL-THO Thin Series Emergency Light is constructed from injection-molded, engineer-grade, 5VA flame retardant thermoplastic. White housing is standard.

ILLUMINATION

The EL-THO Thin Series Emergency Light uses long-lasting, efficient ultra bright white LEDs. Fully adjustable LED lamp heads equipped with 3 white LEDs each. Lamp heads are on track-and-swivel arrangement allowing lamp heads to be fully adjustable.

ELECTRICAL COMPONENTS

Universal voltage input 100-300V operation. LED display indicates AC/ON. An external push button test switch allows maintenance personnel to quickly determine the operational status of the unit. Unit offers surge protected, solid state circuitry.

EMERGENCY OPERATION

Upon failure of the normal utility power, an internal solidstate transfer switch automatically provides uninterrupted emergency operation for at least 90 minutes. If remote head capability is used without connecting additional remote heads, the battery can provide a run-time of 180 minutes. The fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

BATTERY - BATTERY BACKUP

The EL-THO Thin Series Emergency Light is designed with a maintenance-free 3.6V 7200mAh LiFePO4 battery that provides a minimum emergency duration of 90 minutes. Recharge time of the battery is 24 hours.

OPERATIONAL TEMPERATURE

Temperature Ratings

Standard Option

50°F to 104°F


REMOTE HEAD CAPABLE OPTION

The remote head capability option allows the EL-THO unit to supply power to up to two additional (up to 12.8W) 3.6V LED remote heads. The remote heads would then operate on the same emergency mode as the standard units (see Emergency Operation Section).

INSTALLATION

The EL-THO Thin Series Emergency Light is suitable for wall or ceiling mount. Snap together design allows for quick and easy installation. Conduit mount knockout on back plate only.

DIMENSIONS



Weight : 6.00 lb

3170 Scott St, Vista, CA 92081
Phone: 877-352-3948 | Fax: 877-352-3949
info@exitlightco.com