

# COMPACT LED EMERGENCY LIGHT

Code: ELCEL-M



The ELCEL-M series contemporary design features reliable LED performance wrapped into a compact, stylish and economical package.



## FEATURES

- UL 924, NEC, OSHA and NFPA 101 Life Safety Code
- All LED light! No SLA batteries, uses long lasting NiCads that are very low maintenance
- Two fully adjustable, glare-free LED lighting heads
- Injection-molded, high impact, UV-stabilized, UL 94 V-O thermoplastic housing
- Lightweight with snap-together construction for easy installation
- Universal mounting plate with quick-connect feature
- Universal J-box mounting pattern

## WARRANTY INFORMATION

Any component that fails due to manufacturer's defect is guaranteed for 1 year. The warranty only covers products installed and maintained in accordance with the instructions provided by their respective manufacturer and no warranty is made with respect to any of our products that are otherwise installed or maintained. For full warranty details, visit our Warranty Section.

## Conformance to Codes and Standards

The ELCEL-M series is UL listed and meets or exceeds the following: UL 924, NEC, OSHA and NFPA 101 Life Safety Code requirements.

## ORDERING INFORMATION

Series	Housing Color	Operation Type
ELCEL-M	W (White)	BB (Battery Backup)

## CONSTRUCTION

The ELCEL-M Series is constructed from injection molded, Impact-and scratch-resistant and corrosion-proof UL 94 V-0 flame retardant thermoplastic housing. White housing is standard.

## ILLUMINATION

Uses two LED lamp heads each equipped with 8 series-parallel white LEDs. Lamp heads are on track-and-swivel guides. Glarefree lenses provide redundant light source to ensure performance in emergency situations.

## ELECTRICAL COMPONENTS

Dual voltage input 120/277 VAC operation. LED display indicates AC/ON. An external push button test switch with battery backup units allows maintenance personnel to quickly determine the operational status of the unit. Unit offers surge protected, solid state circuitry.

## EMERGENCY OPERATION

Upon failure of the normal utility power, an internal solidstate transfer switch automatically provides uninterrupted emergency operation for at least 90 minutes. The fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.


## BATTERY - BATTERY BACKUP

The ELCEL-M Emergency Lighting series is designed with maintenance-free 3.6V NiCad battery that provides a minimum emergency duration of 90 minutes. Recharge time of the battery is 24 hours. Operation temperature range is 50°F (10°C) to 104°F (40°C)

## INSTALLATION

The ELCEL-M is suitable for wall or ceiling installation via included mounting plate. Snap together design allows for quick and easy installation.

## DIMENSIONS



---

3170 Scott St, Vista, CA 92081  
Phone: 877-352-3948 | Fax: 877-352-3949  
info@exitlightco.com