

EMERGENCY LIGHT - HAZARDOUS CLASS I, DIVISION 2

Code: EL-U-C1D2



FEATURES

- UL 595, 844, 1570. NFPA 101 and 70
- UL Wet location listed (Indoor/Outdoor)
- 120 VAC (60 Hz) input
- Corrosion resistant, copper-free die cast aluminum construction w/baked on epoxy/polyester powder finish
- Exposed hardware is 316 grade stainless steel
- Factory sealed - no external seal required
- Suitable for use in Class I, Division 2 & Class II, Class III
- 4-Pin 42 watts long-life triple-tube compact fluorescent lamp included
- Low voltage disconnect (LVD)
- Maintenance-free sealed battery
- Minimum Start 0°C temperature

WARRANTY INFORMATION

Any component that fails due to manufacturer's defect is guaranteed for 1 year. The warranty only covers products installed and maintained in accordance with the instructions provided by their respective manufacturer and no warranty is made with respect to any of our products that are otherwise installed or maintained. For full warranty details, visit our Warranty Section.



Conformance to Codes and Standards

The LED series is UL listed and meets or exceeds the following: UL 595, 844, 1570. NFPA 101 and 70

ORDERING INFORMATION

Series	Housing Color	Voltage	Operation Type	Conduit Size	Options
EL-U-C1D2	Gray	120VAC	BB (Battery Backup)	3/4"	Emergency Operation
				1"	Ceiling Mount
					Pendant Mount
					Wall Mount

CONSTRUCTION

High-strength, corrosion-resistant, copper-free cast aluminum alloy ballast housing and outlet boxes. Corrosion-resistant, high-strength, fiberglass-reinforced polycarbonate guard. Corrosion- and chemical-resistant baked epoxy exterior surfaces

ILLUMINATION

One 42 watts quad compact fluorescent lamp provides up to 700 lumens of initial light output in emergency mode.

EMERGENCY OPERATION

Emergency Operation available with Battery Backup system provides at least 90 minutes of illumination in emergency mode. Units contain battery that provides the OSHA required 90 minutes of illumination for egress.

INSTALLATION

Suitable for installation on marine environments where equipment is subject to salt water spray, either indoor or outdoor. Large hinge allows for "hands free" wiring and improved heat dissipation of internal components

DIMENSIONS

Height 22"

Diameter 13.813"

Weight 20.00 lb

3170 Scott St, Vista, CA 92081
Phone: 877-352-3948 | Fax: 877-352-3949
info@exitlightco.com