



PHOTOLUMINESCENT EXIT SIGN ALUMINUM HOUSING | RED, GREEN, OR BLACK FACE

Code: PA2



FEATURES

- UL 924, NEC and NFPA 101 Life Safety Code
- Listed for damp location
- No electricity, no batteries required
- Operating Temperature 50°F – 104°F
- Life Expectancy +25 years
- Field installable arrow configuration
- 50, 75, 100 foot viewing distance
- 90 minutes of illumination
- Requires 54 LUX (5-ft candles) of LED, fluorescent, metal halide or mercury vapor light to charge material for 60 minutes
- Explosion proof, weatherproof
- Indoor installation only
- Do not expose to direct sunlight
- No future hazmat disposal needed
- Aluminum frame available

The PA2 is an easy to install electricity free Exit Sign that does not require wiring, or batteries.



WARRANTY INFORMATION

Any component that fails due to manufacturer's defect is guaranteed for 1 year. The warranty only covers products installed and maintained in accordance with the instructions provided by their respective manufacturer and no warranty is made with respect to any of our products that are otherwise installed or maintained. For full warranty details, visit our Warranty Section.

Conformance to Codes and Standards

The PA2 series is UL listed and meets or exceeds the following: UL 924, cUL, and NFPA 101 Life Safety Code requirements.

ORDERING INFORMATION

Series	Sign Color	Viewing Distance	Side Option	Options
PA2	R (Red)	50ft	S (Single Sided)	NF (No Frame)
	G (Green)	75ft	DS (Double Sided)	
	B (Black)	100ft		

CONSTRUCTION

The PA2 exit sign is made from durable rigid aluminum base.

ILLUMINATION

The PA2 exit sign has a viewing visibility range of 50-100 feet (must select desired viewing distance). Provides consistent, uniform illumination.

ELECTRICAL COMPONENTS

The PA2 exit sign does not use nor require any type of electrical components.

EMERGENCY OPERATION

Upon failure of the normal utility power the PA2 exit sign will provide at least 90 minutes of illumination.

*The sign must be charged for a minimum of 60 minutes to become fully operational.

BATTERY - BATTERY BACKUP

The PA2 exit sign does not require batteries to operate.

INSTALLATION

The PA2 exit sign is suitable for wall, ceiling, and side mount installation. For non-framed options, pre-made holes are found on each corner of exit sign for easy wall mount installation or double-sided tape can be used for mounting (not provided). Two self-adhesive chevrons are supplied with each sign that allows for fast and easy field configuration. The mounting bracket supplied, does not come with pre-drilled holes to allow installer to match existing mounting holes if necessary.

DIMENSIONS



Weight : 4.00 lb

3170 Scott St, Vista, CA 92081
Phone: 877-352-3948 | Fax: 877-352-3949
info@exitlightco.com