

LED SINGLE-DOUBLE REMOTE HEAD INDOOR-OUTDOOR 3.6V/9.6V

- By using LED remote heads with your remote capable LED emergency light, you not only lower the cost of operating 2 units, you also lower the cost versus standard incandescent units.
- Self-Testing option allows unit to test every 28 days for 5 minutes and 90 minutes every 6 months.
- Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run.

RHB-WPL1 (Outdoor)	RHB-WPL2 (Outdoor)	RHB-L1 (Indoor)	RHB-L2 (Indoor)
			
<p>Features: UL 924, NEC, OSHA and NFPA 101 Life Safety Code Requirements</p> <p>Adjustable Weatherproof 12 LED Lamp Head</p> <p>Constructed of Gray Spec Grade Die Cast Aluminum</p> <p>For Use with any Remote Head Capable Emergency Light or Exit Sign with matching Voltage</p>		<p>Features: Adjustable 12 LED Lamp Head</p> <p>Constructed of VO flame retardant, high impact thermoplastic housing</p> <p>For Use with any Remote Head Capable Emergency Light or Exit Sign with matching Voltage</p>	
<p>CONSTRUCTION The RHB-WPL is available in a premium grade die-cast aluminum housing. Sealed and gasketed weatherproofing in standard gray.</p> <p>ILLUMINATION The RHB-WPL has long lasting, efficient, ultra-bright white LED lamp heads. High performance chrome-plated metallized reflector and glass lens with 8 or 12 LED's in each lamp head for optimal light distribution. Adjustable LED lamp heads increases center-to-center spacing.</p> <p>ELECTRICAL COMPONENTS Powered from low voltage power source with low voltage wiring (not provided).</p> <p>INSTALLATION The RHB-WPL has a universal mounting base mount to single gang switch box. Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run. Suitable for wall or ceiling mount.</p>		<p>CONSTRUCTION The RHB remote head series is constructed from injection-engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic white finish.</p> <p>ILLUMINATION Smooth thermoplastic reflector with plastic lens for optimal light distribution. Adjustable lamp head with 12 LED's that provides increased center-to-center spacing.</p> <p>ELECTRICAL COMPONENTS Powered from low voltage power source with low voltage wiring (not provided).</p> <p>INSTALLATION The RHB remote head includes a universal mounting base plate with mounting hardware. The distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run. Suitable for wall or ceiling mount</p>	
Dimensions			
Width: 4.25" Height: 6.625"	Width: 10.375" Height: 6.75" Length: 4.25"	Width: 4.5" Height: 4.875" Length: 5.875"	Width: 4.5" Height: 5" Length: 5.875"