

VANDAL RESISTANT, WET AREA EXIT SIGN

Code: LEDVR



FEATURES

- CSA, ETL, IP66 & Title 20
- Listed for wet and hose-down location
- Since this item is made to order, please expect a 6 week lead time
- Sealed nickel-cadmium battery: Provides a minimum of 90-minutes emergency operation
- 120/277/347 VDC input
- Constructed from .420 thick, heavy duty-cast aluminum
- High abuse clear polycarbonate shield
- Field selectable chevrons
- Standard operating temperature: 32°F to 113°F (0°C to 45°C)
- Optional cold-weather feature: -40°F to 113°F (-40°C to 45°C)
- Allows for wall/flush, ceiling, and flagpole/end installation

WARRANTY INFORMATION

Any component that fails due to manufacturer's defect is guaranteed for 1 year. The warranty only covers products installed and maintained in accordance with the instructions provided by their respective manufacturer and no warranty is made with respect to any of our products that are otherwise installed or maintained. For full warranty details, visit our Warranty Section.

Conformance to Codes and Standards

The LEDVR series is meets or exceeds the following: CSA, ETL, Wet Location IP66 & Title 20

Vandal Resistant, Wet Location Exit Sign featuring a high abuse clear polycarbonate shield, energy efficient LEDs, and a maintenance free NiCad battery.



ORDERING INFORMATION

Series	Housing Color	Sides	Voltage	Operation Type	Options
LEDVR-R (Red)	Black	Single	120/277/347V	AC (AC Only)	Audible Alarm
LEDVR-G (Green)	White	Double		BB (Battery Backup)	Visual Alarm
					Fire Alarm Interface

CONSTRUCTION

The ultra heavy duty design and appearance of the LEDVR series exit warns potential vandals that this is no regular sign. The stencil is protected by a 1/8" thick, impact resistant polycarbonate shield that is recessed into the housing and fastened with 4 tamper resistant screws. The LEDVR offers a contemporary look and durability like no other.

ILLUMINATION

The LEDTR series uses ultra bright, energy efficient red or green LEDs.

ELECTRICAL COMPONENTS

The LEDTR has a 120/277V input. Solid state charger, auto-test, and transfer are standard on self powered units. The self powered version comes standard with an external LED status indicator and test switch.

EMERGENCY OPERATION

Upon failure of the normal utility power, an internal solidstate transfer switch automatically provides uninterrupted emergency operation for at least 90 minutes. The fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.


BATTERY - BATTERY BACKUP

The LEDVR series is designed with a maintenance free, sealed Nickel-Cadmium battery providing a minimum emergency duration of 90 minutes. The battery operating temperature without the internal heater/ thermostat option is 40°C maximum and 7.2°C minimum; with the internal heater (IH) option the minimum battery operating temperature is -20°C.

INSTALLATION

The WLT is suitable for surface wall and top mounting via included canopy. Snap together design allows for quick and easy installation. Knock-outs provided for conduit feed applications. Perforated chevron arrows allow for on-site setup.

DIMENSIONS



Weight : 12.00 lb

3170 Scott St, Vista, CA 92081
Phone: 877-352-3948 | Fax: 877-352-3949
info@exitlightco.com