



50' VIEW PHOTOLUMINESCENT EXIT SIGN | RIGID PLASTIC BASE | RED OR GREEN LETTERING | BLACK FRAME

Code: PA1



The PA1 Series Exit Sign is an easy to install, power-free sign that does not require wiring, batteries, nor recycling.



FEATURES

- UL 924, NEC and NFPA 101 Life Safety Code
- Listed for damp location
- No electricity, no batteries required
- Life Expectancy +25 years
- Operating Temperature 50°F – 104°F
- Field installable arrow configuration
- 50 foot viewing distance
- 90 minutes of illumination
- Requires 54 LUX (5-ft candles) of LED, fluorescent, metal halide or mercury vapor light to charge material for 60 minutes
- Explosion proof, weatherproof
- Indoor installation only
- Do not expose to direct sunlight
- No future hazmat disposal needed

WARRANTY INFORMATION

Any component that fails due to manufacturer's defect is guaranteed for 1 year. The warranty only covers products installed and maintained in accordance with the instructions provided by their respective manufacturer and no warranty is made with respect to any of our products that are otherwise installed or maintained. For full warranty details, visit our Warranty Section.

Conformance to Codes and Standards

The PA1 series is UL listed and meets or exceeds the following: UL 924, cUL, and NFPA 101 Life Safety Code requirements.

ORDERING INFORMATION

Series	Letter Color
PA1	R (Red)
	G (Green)

CONSTRUCTION

The PA1 Series Exit Sign has a thin, low profile construction with 50' visibility. It has a durable plastic photoluminescent panel with a black plastic frame. This photoluminescent exit sign is explosion-proof for areas requiring explosion-proof exit signage.

ILLUMINATION

The PA1 Series Exit Sign has a viewing visibility of 50'. Provides consistent, uniform illumination.

ELECTRICAL COMPONENTS

The PA1 Series Exit Sign does not use nor require any type of electrical components.

EMERGENCY OPERATION

Upon failure of the normal utility power the PA1 exit sign will provide at least 90 minutes of illumination.

*The sign must be charged for a minimum of 60 minutes to become fully operational.

BATTERY - BATTERY BACKUP

The PA1 Series Exit Sign does not require a battery to operate.

INSTALLATION

The PA1 Series Exit Sign is suitable for wall mount. The included black frame has holes on each corner for easy wall mount installation. If black frame is not needed, double sided tape (not included) can be used for wall installation. Two (2) self-adhesive arrows are included to show proper path of egress.

DIMENSIONS



Weight : 4.00 lb

3170 Scott St, Vista, CA 92081
Phone: 877-352-3948 | Fax: 877-352-3949
info@exitlightco.com